

DryFireMag[®] for Glock Instructions

WARNING!


Check to be sure the gun chamber is empty
BEFORE inserting the DryFireMag®



Scan for instructions with video!



Insert **DryFireMag**® after racking the slide.



DryFireMag® Lever (blue) must be behind Trigger Bar (red).

Figure 2

THIS DEVICE IS SIMPLE TO USE, BUT IT MUST BE INSTALLED PROPERLY.

Make sure your weapon is clear of ammo.

- Pull the slide <u>all the way</u> back on the firearm, and <u>let it go</u> (in other words, "cycle" the slide). (NEVER RACK THE SLIDE WITH THE <u>DryFireMag® INSERTED</u>)
- Insert the DryFireMag®completely into position. This will require a firm "bump" with the palm of the hand. (See Figure 1)
- The <u>first</u> trigger pull will be heavy, as it is releasing the firing pin and the <u>DryFireMag®</u> together.*
- Aim in a safe direction. It's ready to go!

*Once the **DryFireMag**® is in position, the first trigger pull will be extra heavy because you will be releasing the pistol's firing pin and activating the **DryFireMag**® mechanism. After the first pull, the the **DryFireMag**® will be engaged and will provide a total dry fire practice experience.

There are a few slight adjustments that can be made by the user. If you desire a different pull, **go to** www.DryFireMag.com and watch the demonstration. If you need further assistance, or have questions, please contact us through the "contact" page on our website.

Be sure to register your DFM @ www.dryfiremag.com/dryfiremagproduct-registration/ PLEASE NOTE: Since there are multiple modifications that can be made to different pistols, your DryFireMag® may not function as you have seen it work in the videos. This is probably not due to a malfunction in the DryFireMag® but to the wide range of variations possible in firearms. Because of this, the DryFireMag® may require an adjustment to meet your unique application. If you have more than one pistol, this may even vary slightly from one pistol to another.

To change the feel of the trigger pull when using the **DryFireMag®** to either a heavier or lighter pull, the coil spring will need to be changed.

Your **DryFireMag**® has been tested and adjusted to the standard trigger pull of **5.5 #.**An extra spring is included for a lighter trigger pull. A Spring Kit with springs of varying weights is available for use in the **DryFireMag**® **for Glock** at <u>www.dryfiremag.com/products</u>.

(Remember to always wear safety glasses when changing springs).

Adjusting the amount of pre-travel (the point of the simulated release of the firing pin).

- 1. Locate the #10 Allen wrench and the top hole on the back of the magazine.
- 2. To shorten the trigger pre-travel, turn the set screw clockwise 1/8 of a turn. Reinsert the DryFireMag® and test. If pre-travel is still not short enough, repeat adjustment and retest. Turn this adjustment a maximum of one complete turn unless specifically advised by DFM.
- 3. To lengthen the trigger pre-travel, turn the set screw counter clockwise 1/8 of a turn. Reinsert the DryFireMag® and test. If an even longer pre-travel is desired, repeat adjustment and retest. Turn this adjustment a maximum of one complete turn unless specifically advised by DFM.

If you desire assistance to make the adjustments, contact DryFireMag® to schedule a personal appointment by phone, video chat, or email. **Call** (208) 702-7030 , **Toll Free** at (844) 844-4600 , or email TechSupport@DryFireMag.com

Customer satisfaction is our #1 goal!

Satisfaction Guaranteed: If you are not completely satisfied with your **DryFireMag®**, you may return it within **30 days** of having received it for a full refund. Upon request, **DryFireMag®**, **LLC** will send a return label. We cannot provide postage for customers outside of the USA and its territories. Your refund will be issued when the product is received in an unaltered and undamaged condition.

Warranty: DryFireMag[®] will repair or replace your DryFireMag[®] at our option within 1 year of purchase for any malfunction of the DryFireMag[®] due to workmanship or faulty materials. Any malfunction due to tampering or physical damage will not be covered by this warranty. This will be determined at the sole discretion of DryFireMag, LLC. This warranty covers the original purchase price of the DryFireMag[®] Contact us through the DryFireMag.com "Contact" page and choose the link that applies.

Anyone using the **DryFireMag**[®] assumes full responsibility for its use. DryFireMag LLC. assumes no responsibility for any damage to property, or personal injury due to any use of this device.



